

Step XL & L

2020

WOOD
product
data
sheet



pattern: 1 strip

Step is a selection of sophisticated and elegant designs in superior quality construction. Combination of brushed structure, colours and innovative technology of digital print on parquet will provide distinctive beauty and comfort to any room.

board size: Step XL 1200/1000 x 164 x 14 mm
Step L 1200/1000 x 140 x 14 mm

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Pure / White	550184001	OAK ROYAL AZURE BR XL 1200	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184002	OAK ROYAL AZURE BR L 1200	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184003	OAK ROYAL AZURE BR XL 1000	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184004	OAK ROYAL AZURE BR L 1000	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Pure / Antique White, Grey	550184005	OAK ROYAL ANTIQUE WHITE BR XL 1200	Oak	UNI Robust	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184006	OAK ROYAL ANTIQUE WHITE BR L 1200	Oak	UNI Robust	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184007	OAK ROYAL ANTIQUE WHITE BR XL 1000	Oak	UNI Robust	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184008	OAK ROYAL ANTIQUE WHITE BR L 1000	Oak	UNI Robust	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Classic / Nature	550184013	OAK BARON BR XL 1200	Oak	UNI Nature	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184014	OAK BARON BR L 1200	Oak	UNI Nature	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184015	OAK BARON BR XL 1000	Oak	UNI Nature	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184016	OAK BARON BR L 1000	Oak	UNI Nature	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Brown / Mocha	550184021	OAK BARON SIENNA BR XL 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184022	OAK BARON SIENNA BR L 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184023	OAK BARON SIENNA BR XL 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184024	OAK BARON SIENNA BR L 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Classic / Honey	550184025	OAK BARON CORAL BR XL 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184026	OAK BARON CORAL BR L 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184027	OAK BARON CORAL BR XL 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184028	OAK BARON CORAL BR L 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Brown / Cocoa	550184029	OAK BARON BROWN BR XL 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184030	OAK BARON BROWN BR L 1200	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184031	OAK BARON BROWN BR XL 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184032	OAK BARON BROWN BR L 1000	Oak	UNI Rustic	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Brown / Mocha	550184052	OAK BARON COPPER BR XL 1200	Oak	UNI Nature	Yes	No	PL	30	Yes	No	midi	DoP 2702-0012-2016-12
	550184042	OAK BARON COPPER BR L 1200	Oak	UNI Nature	Yes	No	PL	30	Yes	No	midi	DoP 2702-0012-2016-12
	550184053	OAK BARON COPPER BR XL 1000	Oak	UNI Nature	Yes	No	PL	30	Yes	No	midi	DoP 2702-0012-2016-12
	550184043	OAK BARON COPPER BR L 1000	Oak	UNI Nature	Yes	No	PL	30	Yes	No	midi	DoP 2702-0012-2016-12

product line/ subline	code	product name	wood specie	grade	digital print	stain	surface lacquer	gloss level	brushed	heat treatment	bevel	dop number
Essential Classic / Nature	550184047	OAK BARON RUSTIC BR XL 1200	Oak	UNI Rustic	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184048	OAK BARON RUSTIC BR XL 1000	Oak	UNI Rustic	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184049	OAK BARON RUSTIC BR L 1200	Oak	UNI Rustic	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184050	OAK BARON RUSTIC BR L 1000	Oak	UNI Rustic	No	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184054	OAK ROYAL GREY BR XL 1200	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Pure / Antique White, Grey	550184056	OAK ROYAL GREY BR L 1200	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184055	OAK ROYAL GREY BR XL 1000	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184057	OAK ROYAL GREY BR L 1000	Oak	UNI Robust + UNI Rustic	Yes	No	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
Essential Pure / White	550184081	OAK SNOW BR XL 1200	Oak	UNI Robust +UNI Rustic +UNI Nature	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184083	OAK SNOW BR L 1200	Oak	UNI Robust +UNI Rustic +UNI Nature	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184082	OAK SNOW BR XL 1000	Oak	UNI Robust +UNI Rustic +UNI Nature	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12
	550184084	OAK SNOW BR L 1000	Oak	UNI Robust +UNI Rustic +UNI Nature	No	Yes	PN	9	Yes	No	midi	DoP 2702-0012-2016-12

PN - Proteco Nature PL - Proteco Lacquer

installation

- Floating or glue down installation.
- Surface must be clean, dry and flat.
- Relative air humidity: 30-50%.
- Room temperature: 18-24°C.

maintenance

- The finishing technology used for Tarkett floors makes them the best choice for easy maintenance. To preserve all the beauty of your Tarkett wood flooring, simply follow simple protection suggestions.

- 1 – WET MOPPING OR VACCUMING: Wet mopping with almost dry cloth.
Use protective pads when moving furniture
- 2 – DRY CLEANING: Dry mopping & vaccum cleaning
- 3 – REGULAR CLEANING: Tarkett Cleaner
- 4 – PERIODICAL CLEANING: Tarkett Refresher



T-LOCK
Tarkett lock, glue-free locking system

AQUA GUARD
Extended liquid resistance at the short side of boards connection

HEALTHY FLOORS
Lacquer properties prevent bacteria reproduction

ENVIRONMENTAL COMMITMENT
Environmental responsibility throughout all processes (C2C, FSC, ISO14001)

WARRANTY
30 years residential warranty



underfloor heating

- Since wood is a living material, during the heating season, minor gaps might develop between wood flooring boards due to interior climate conditions. These gaps cannot be related to product quality. Boards movement can be minimized by keeping temperature level at approx. 20° C and a relative air humidity at approx. 50 %.
- *Not suitable for the wood species beech and maple

technical data

product description: Multilayer 14 mm parquet with surface coating for indoor use (EN 13489)

essential characteristics	performance	harmonised technical specification
A – Reaction to fire	Dfl-s1	EN 14342:2013
the minimum mean density	500 kg/m ³	
the minimum overall thickness	14 mm	
the end-use condition to be applied	glued to the substrate or with or without air gap underneath	
B – Formaldehyde emission	E1	
C – Content of pentachlorophenol	< 5 ppm	
D – Breaking strength	NPD	
E – Slip resistance	NPD	
G – Thermal conductivity	0,11 W/m K	
H – Biological durability	Class 1	

size and package

size and package characteristics	value
Thickness (mm)	~14
Width (mm)	164/140
Length (mm)	1200/1000
Wear layer thickness (mm)	~2,8
Boards/pack	6
m ² /pack	1200x164x6 =1,182 m ² ; 1200x140x6=1,008 m ² 1000x164x6=0,984 m ² ; 1000x140x6=0,840 m ²
m ² /pallet	1200x164x6=70,92 m ² ; 1200x140x6=70,56 m ² 1000x164x6=59,04 m ² ; 1000x140x6=50,40 m ²
Weight/m ² (kg)	~7,53 / ~7,36

design overview



OAK SNOW BR



OAK ROYAL AZURE BR



OAK ROYAL
ANTIQUÉ WHITE BR



OAK BARON BR



OAK BARON SIENNA BR



OAK BARON CORAL BR



OAK BARON BROWN BR



OAK BARON COPPER BR



OAK BARON RUSTIC BR



OAK ROYAL GREY BR